

## UV DRYER

- Compact Design
- Single Phase for 12 inch / 3 Phase for 18 inch
- Easy to operate
- PTFE Teflon coated conveyor belt
- End Less Conveyor belt
- Variable Speed Control



	Size : 12"	Size : 18"
<b>Curing Speed</b>	0-6 Mt/Min	0-6 Mt/Min
<b>Lamp Capacity</b>	200 W/ Inch	200 W / Inch
<b>Power Supply</b>	220 V AC/16 Amps/1 PH/50 HZ	440 V AC/ 32 Amps/3 PH/ 50 HZ
<b>Power Consumption</b>	2.6 kw	4.5 kw
<b>Size</b>	750 (w) x 960 (l) x 420 (h)	914(w)x1397 (l) x 990 (h)
<b>Max Conveyor Speed</b>	22.5m/ Per min	23.5m/ Per min

## AUTO CREASER



Feeding System .....	Bottom suction feed
Max. Sheet Size .....	700mm x 330mm
Min. Sheet Size (in automatic mode).....	210mm x 140mm
Max. Paper Thickness .....	0.4mm
Min. Distance Between Creases .....	0.1mm
Min. Crease Distance from Leading Edge .....	2.5mm
Min. Crease Distance from Tail Edge .....	35mm
Speed per Hour .....	8500
Power Requirement .....	1 phase